## IN THE CLAIMS:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

- 1. (Currently Amended) A tie-down device, comprising
- a first member having a bottom panel;
- a first extended region emanating from said bottom panel;

an affixing means for attaching said bottom panel to a member received on said bottom panel; and

an anchoring means for affixing said first extended region to a structure in a steadfast manner; and

a second extended region emanates from said bottom panel in a direction opposing said first extended region, and a second anchoring means affixing said second extended region to a structure in a steadfast manner.

- 2. (Currently Cancelled) The device of Claim-1, wherein a second extended region emanates from said bottom panel in a direction opposing said first extended region, and a second anchoring means affixing said second extended region to a structure in a steadfast manner.
- 3. (Currently Amended) The device of Claim 2 1, wherein a first panel emanates from said bottom panel in a substantially perpendicular fashion therefrom; said first panel receiving

07/18/2005 12:27 3104468979 MILORD ASSOCIATES PAGE 07/21

said affixing means therethrough, thereby affixing said first panel to said member in a secure manner.

- 4. (Currently Amended) The device of Claim 2 1, wherein a first panel emanates from said bottom panel in a substantially perpendicular fashion therefrom, and a second panel emanates from said bottom panel in opposing relation to said first panel such that a guide is created therebetween for receiving said member, and at least one of said affixing means attaches said first panel to a first face of said member and at least one of said affixing means attaches said second panel to a second face of said member.
  - 5. The device of Claim 4, wherein said member is a wood beam.
- 6. The device of Claim 4, wherein said member is selected from a group consisting of a truss and a gable end truss.
- 7. The device of Claim 4, wherein said affixing means is selected from a group consisting of a nail, a threaded element, a nut and bolt apparatus.
  - 8. The device of Claim 4, wherein said first member is constructed of metal.
- 9. The device of Claim 4, wherein, in combination, said structure is a preform wall containing a curable material, said anchoring means passing through an aperture in each of said first and second extended regions and being received and bound within said curable material.

a second member constructed from a unitary piece of material having a bottom plate;

an extended section-emanating from said bottom plate in a substantially similar plane;

an affixing means for attacking said second member to a member resting on said bottom

plate; and

an anchoring means for affixing said first extended section to a structure in a steadfast

- 11. (Currently Cancelled) The system of Claim 10, wherein a first sheet extends in a vertical direction from a first border of said extended section, and a third sheet extends from said first sheet in a perpendicular fashion, said affixing means attaching said third sheet to said member in a secure manner.
  - 12. (Currently Cancelled) The system of Claim 10, further comprising:

a first sheet extends in a vertical direction from a first border of said extended section and a second sheet extends in a vertical direction from a second border of said-extended section;

a third sheet extending from said first sheet in a perpendicular fushion, said affixing means attaching said third sheet to said member in a secure manner;

a fourth-sheet extending from said-second sheet in a perpendicular fashion, said affixing means attaching said fourth sheet to said member in a secure-manner.

13. (Currently Cancelled) The system of Claim 11, wherein at least a hole is defined by

07/18/2005 12:27 3104468979 MILORD ASSOCIATES PAGE 09/21

said extended section-and receives an elongated portion of said anchoring means therethrough and anchors said second member to said structure in a steadfast manner.

- 14. (Currently Cancelled) The system of Claim 12, wherein at least a first plate emanates from said bottom plate in a vertical direction and is distal to said extended section such that a first channel is defined by said first plate, said bottom plate; said third sheet and said fourth sheet, and said member being received within said channel.
- 15. (Currently Cancelled) The system of claim 14, wherein said first plate is connected to said first member by at least one of said affixing means.
- 16. (Currently Cancelled) The system of claim 14, wherein said structure is a preform wall containing a curable material, said anchoring means passing through said hole is received and bound within said curable material.
- 17. (Currently Cancelled) The system of claim 14, wherein said-second member is constructed of a metal.
- 18. (Currently Cancelled) The system of claim 14, wherein said member is selected from a group consisting of a truss and a gable end truss.
- 19. (Currently Amended) A method for attaching trusses to a preform wall structure having an outer wall and an inner wall wherein a curable material is poured therebetween, the

07/18/2005 12:27 3104468979 MILORD ASSOCIATES PAGE 10/21

method comprising:

providing a first member of unitary construction having a bottom panel;

providing a first extended region from said bottom panel;

providing a second extended region extending from said bottom panel in an opposite

direction to said first extended region;

providing a first panel attached to said bottom panel;

placing said truss upon said bottom panel;

attaching said first panel to said truss with an affixing means;

anchoring said first extended region to said curable material with an anchoring means.

20. The method of claim 19, further comprising the steps of:

defining an aperture within said extended region;

inserting an elongated portion of said anchoring means through said aperture and into said curable material;

engaging a head portion of said anchoring means upon said extended region.